

Hard work with ease
TransPro 3440



Versatile



Efficient



Unique

Versatile & efficient, every day all year round

TransPro 3440



With experience

The Belos TransPro 3440 is designed to meet the demands of the Operator, Service Department and Management. From our years of experience and with input from customers, Belos has developed a new machine in the compact class. Although diminutive in size the TransPro 3440 has full-grown features as an Implement Carrier.

Profitable machine systems

With compatibility to a wide variety of interchangeable implements the TransPro 3440 is extremely versatile, making it a true year-round machine. High fleet utilization and a high return on investment are significantly increased because of the four season adaptability.

The spacious cab offers a comfortable environment designed to minimize operator fatigue. Outstanding all around visibility offers a safe working environment, while maintaining a low noise level for the operator. Cabin features include a cushioned flat floor for minimal vibration with abundant





leg room, smooth hydrostatic pedals, adjustable steering wheel, heat and air conditioning, and adjustable ergonomically positioned controls. These features create an unmatched operator experience in the compact field.

Hard work

Easy accessibility to components for service and maintenance make the Belos a preferred choice for the service technician. The TransPro 3440 is equipped with a 34 hp Kubota diesel engine that is both fuel efficient and environmentally friendly with low exhaust emissions. The balanced weight to horse power ratio combined with 4 wheel hydrostatic drive give stability and traction to the articulated steered machine.

Human - Machine - Environment

World leading technologies are used to design and manufacture the new Belos TransPro 3440 that offers owners Comfort, Safety, Maneuverability, Reliability, Dependability, Easy Maintenance, and Versatility for a Low Cost of Ownership.



Specification

TransPro 3440

Dimensions

| | |
|----------------|-------------------|
| Overall length | 2395 mm / 90.6 in |
| Overall width | 1080 mm / 42.5 in |
| Overall height | 1970 mm / 77.6 in |
| Wheel base | 1300 mm / 51.2 in |
| Min Weight | 900 kg / 1984 lb |
| Max Weight | 1650 kg / 3638 lb |



Frame

| | |
|-----------------------------|---|
| Type | Articulated-steering, welded with closed tubular sections |
| Steering | Hydraulic |
| Steering angle | 52 degree |
| Loose joint at max steering | 0 degree |
| Loose joint at min steering | 12 degree |
| Max load in front | 551 lb 19.6 in in front of front axel |
| Max load in center | 1543 lb |
| Max load in rear | 661 lb 19.6 in behind rear axel |

Transmission

| | |
|--------------------|---|
| Type | Hydrostatic (HST) hydraulic engine in each wheel 4 WD |
| Max transportspeed | 12.5 mph |
| Cruise control | Option on demand |
| Travelling brakes | Hydrostatic on all 4 wheels |
| Parking brake | Mechanical on all 4 wheels |

Engine

| | |
|------------------------------|------------------------|
| Type | Kubota D1105T |
| Power output, gross | 24.5 kW @ 3000 rpm |
| Power output net (SAE J1349) | 23.5 kW @ 3000 rpm |
| Fuel | Diesel |
| Fuel tank | 11 us gal / 9.2 uk gal |
| Emissions | Step 3A (97/68 EC) |
| Noise level in cabin | <79 dBA |

Main PTO

| | |
|---------------|----------------------|
| Type | Hydraulic |
| Capacity, max | 10.5 gal/m, 3481 psi |

Secondary, PTO

| | |
|---------------|---------------------|
| Type | Hydraulic |
| Capacity, max | 0-4 gal/m, 2320 psi |

Other PTO

| | |
|---------------|-------------------|
| Capacity, max | 4 gal/m, 1958 psi |
|---------------|-------------------|

For more information and complete accessories-list please visit: www.belos.com or contact your dealer.



BELOS • P.O. BOX 1006 • SE-573 28 TRANÅS
TEL. +46 (0)140 677 00 • FAX +46 (0)140-678 01 • www.belos.com

Dealers:

